M

SERIES International Workshop Role of Seismic Infrastructures in Seismic Rehabilitation





Earthquake Engineering Experimental Facility for Research and Public Outreach

by
Ece Eseller-Bayat
Assistant Professor
Istanbul Technical University
Istanbul, Turkey





OUTLINE

- 1. Earthquakes and Devastating Effects
- 2. Reducing the Seismic Risk
- 3. EQ Engineering Experimental Facility at NEU
- 4. Projects conducted using the facility
- 5. Public Outreach and Educational Use of the Facility
- 6. Conclusion

1. Earthquakes and Devastating Effects

Adapazari EQ, 1999, M7.9 death toll:45000



Haiti EQ, 2010, M7.0 death toll:316000



Courtesy of Ayhan Irfanoglu





Courtesy of National Turk



Courtesy of Abdurrahman Antakyali



Tohoku Japan EQ, 2011, M9.0 death toll:22000

Courtesy of Reuters

2. Reducing the Seismic Risk

Learning from Earthquakes: Damaged and undamaged structures



Understanding earthquakes and its effects on our built environment:

Analytically and Experimentally



Finding solutions and remediation



Testing the solutions
Analytically and Experimentally

Large-Scale Earthquake Engineering Testing Facilities are efficient in testing more real field problems and the solutions for mitigation

3. Earthquake Engineering Measurement Facility at Northeastern University, Boston MA

1-D Shaking Table (MTS)



- ≥ 1.5 x 2.0 m
- ➤ 0-50 Hz
- ➤ 25 kN load capacity
- \geq ± 12.7 cm lateral displacement capacity
- ➤NI-DAQ data acquisition card
- ➤ LAbVIEW data processing software

3. Earthquake Engineering Measurement Facility at Northeastern University, Boston MA


Crossbow Accelerometers (1g, 2g, 4g)




Linear Variable Displacement Transducer (LVDT)




P and S wave measurement equipment




PDCR 81 Miniature Pore Pressure Transducer




Bender Elements and Bender Disks for S and P Wave Measurements






3. Earthquake Engineering Measurement Facility Cont'd

Cyclic Simple Shear Liquefaction Box (CSLLB)










3. Earthquake Engineering Measurement Facility Cont'd

Cyclic Simple Shear Liquefaction Box (CSLLB)




- Fixed to an outsider beam
- ➤ 2 rotating (RW) and 2 fixed walls (FW)
- Flexible sealant btw the RW, FW and the bottom plate
- > up to 1% strains



3. Earthquake Engineering Measurement Facility Cont'd

Cyclic Simple Shear Liquefaction Box (CSLLB) Modal analysis






4. Projects Conducted using the EQ Eng. Experimental Facility

- 1. Induced Partial Saturation (IPS) for Liquefaction Mitigation (NSF Award #: CMS-0509894)
- 2. Foundation Isolation for Seismic Protection Using a Smooth Synthetic Liner (NSF granted)
- 3. Soil Isolation for Seismic Protection Using a Smooth Synthetic Liner (NSF granted)
- 4. Evaluation of a Mechanical Isolator for Protecting Four MFA Sculptures Against Earthquakes in Nagoya, Japan

1-Induced Partial Saturation (IPS) for Liquefaction Mitigation Problem



Liquefaction induced bearing capacity failure of a building after Adapazari EQ, 1999




$$\sigma'_f$$
 $u_f = u_0 + \Delta u$

Air-Entrapped Sand

$$\sigma'_{f} = \sigma'_{0} - \Delta u = 0$$
 $r_{u} = \Delta u / \sigma'_{0}$
 $\sigma'_{f} = \sigma'_{0} (1 - r_{u}) = 0$
 $1 - r_{u} = 0$
 $r_{u} = \Delta u / \sigma'_{0} = 1$

Research Goal



Saturated Sand

1-Induced Partial Saturation (IPS) for Liquefaction Mitigation


- IPS Techniques Implemented in the Laboratory
- Controllable Degree of Saturation
- Uniform Distribution of Gas Bubbles


Sodium Perborate monohydrate

$$2(\text{NaBO}_3.\text{H}_2\text{O}) + 2\text{H}_2\text{O} \longrightarrow 2\text{H}_2\text{O}_2 + 2\text{BO}_3^{-3} + 2\text{Na}^+ + 4\text{H}^+$$


$$2\text{H}_2\text{O}_2 \longrightarrow 2\text{H}_2\text{O} + \text{O}_2$$

$$\underline{\text{Hydrogen Peroxide}}$$





$$S = 40-90\%$$




Average Particle Size: 0.3-0.4 mm

Average Bubble Size: 0.18 mm

1-Induced Partial Saturation (IPS) for Liquefaction Mitigation

Integrated Experimental Setup for Evaluation of Cyclic Response of Fully and Partially Saturated Sands





PDCR 81 Pore Pressure Transducer




1-Induced Partial Saturation (IPS) for Liquefaction Mitigation

■ Excess Pore Water Pressures in Partially Saturated Sands






- Cyclic Simple Shear Strains with amplitudes =0.01-0.3% applied on specimens with
 - $D_r = 20-65\%$
 - > S=100-45%
- \blacksquare r_{umax} is reduced as S decreases
- N_{max} gets larger as S decreases



Number of Strain Cycles, N

1-Induced Partial Saturation (IPS) for Liquefaction Mitigation

$$r_u = f(S, D_r, , ', M)$$



Number of Strain Cycles, N


$$\underbrace{\left(1\right) r_{u \max}}_{l \max} = \underbrace{\left[\sqrt{S} \times e^{-\left[\frac{1-S}{0.54}\right]^{4}}\right]}_{l \max} \left[1 - 8.75 \times (D_{r} - 0.2) \times (1-S) \times e^{\left[-\frac{(1-S)^{2}}{2 \times (1-S_{md} \times (0.2/D_{r})^{2})^{2}}\right]}\right]} \left[1 - 1.75 \times (-\log \frac{\gamma}{0.001}) \times (1-S) \times e^{\left[-\frac{(1-S)^{2}}{2 \times (1-S_{mg})^{2}}\right]}\right] \right] \left[1 - 1.75 \times (-\log \frac{\gamma}{0.001}) \times (1-S) \times e^{\left[-\frac{(1-S)^{2}}{2 \times (1-S_{mg})^{2}}\right]}\right] \left[1 - 1.75 \times (-\log \frac{\gamma}{0.001}) \times (1-S) \times e^{\left[-\frac{(1-S)^{2}}{2 \times (1-S_{mg})^{2}}\right]}\right] \left[1 - 1.75 \times (-\log \frac{\gamma}{0.001}) \times (1-S) \times e^{\left[-\frac{(1-S)^{2}}{2 \times (1-S_{mg})^{2}}\right]}\right] \left[1 - 1.75 \times (-\log \frac{\gamma}{0.001}) \times (1-S) \times e^{\left[-\frac{(1-S)^{2}}{2 \times (1-S_{mg})^{2}}\right]}\right] \left[1 - 1.75 \times (-\log \frac{\gamma}{0.001}) \times (1-S) \times e^{\left[-\frac{(1-S)^{2}}{2 \times (1-S_{mg})^{2}}\right]}\right] \left[1 - 1.75 \times (-\log \frac{\gamma}{0.001}) \times (1-S) \times e^{\left[-\frac{(1-S)^{2}}{2 \times (1-S_{mg})^{2}}\right]}\right] \left[1 - 1.75 \times (-\log \frac{\gamma}{0.001}) \times (1-S) \times e^{\left[-\frac{(1-S)^{2}}{2 \times (1-S_{mg})^{2}}\right]}\right] \left[1 - 1.75 \times (-\log \frac{\gamma}{0.001}) \times (1-S) \times e^{\left[-\frac{(1-S)^{2}}{2 \times (1-S_{mg})^{2}}\right]}\right] \left[1 - 1.75 \times (-\log \frac{\gamma}{0.001}) \times (1-S) \times e^{\left[-\frac{(1-S)^{2}}{2 \times (1-S_{mg})^{2}}\right]}\right] \left[1 - 1.75 \times (-\log \frac{\gamma}{0.001}) \times (-\log \frac{\gamma}{$$


$$2) r_u = r_{u \max} \times f\left(\frac{N}{N_{\max}}\right)$$


where
$$f\left(\frac{N}{N_{\text{max}}}\right)$$
 is a function of S, D_r, γ , σ ', M

1-Induced Partial Saturation (IPS) for Liquefaction Mitigation

r_{umax} Model








- ➤ An alternative low- cost seismic protection solution
- ➤ Within several synthetic materials tested, "geotextile/UHMWPE" found to be the most efficient due to:
 - ➤ low friction coefficient (0.11) with slightly higher static friction coefficient than dynamic friction coefficient (0.06-0.08).
 - ➤ Independent of the sliding velocity, little effect of normal stress at low values (40-100 kPA), number of cycles or sliding distance.


2-Foundation Isolation for Seismic Protection Using a Smooth GeoSynthetic Liner







➤ A single story model tested under 3 records of 1989 Loma Prieta Earthquake


2-Foundation Isolation for Seismic Protection Using a Smooth GeoSynthetic Liner Capitola Record








- >Transmitted accelerations stayed more or less around 0.1 g
- The peak drift of the foundation isolated model is much smaller than the non-isolated and remains almost constant




(a) Soil Isolation for buildings





(b) Soil Isolation for reclaimed land

- > the liner is placed within the soil profile to absorb seismic energy before it arrives at the ground
- ➤ horizontal earthquake energy is dissipated through slip deformations along the liner

3-Soil Isolation for Seismic Protection Using a Smooth GeoSynthetic Liner









179 cm x 46 cm x 46 cm Plexiglas tank


➤ Both cylindirical and tub-shaped liners were tested and tub-shaped liner was found to be more effective.



- ➤ Both harmonic and earthquake excitations were applied.
- ➤ Under Santa Cruz record scaled up to 0.8g, when the peak acceleration of the table was greater than 0.2g, the peak transmitted accelerations in the central region of the sand were much smaller than the peak table accelerations



- ➤ Significant reductions in spectral accelerations
- ➤ Side effects diminished in spectral accelerations





- Experimental results are very important to first understand the physical behaviors however have constrains in terms of side effects or the size of the models
- Analytical studies should confirm the field scale applications
- ➤ Effect of H/D on transmitted accelerations determined analytically

4-Evaluation of a Mechanical Isolator for Protecting Four MFA Sculptures Against Earthquakes in Nagoya, Japan




Isolated Building Response






4-Evaluation of a Mechanical Isolator for Protecting Four MFA Sculptures Against Earthquakes in Nagoya, Japan



4-Evaluation of a Mechanical Isolator for Protecting Four MFA Sculptures Against Earthquakes in Nagoya, Japan



4-Evaluation of a Mechanical Isolator for Protecting Four MFA Sculptures Against Earthquakes in Nagoya, Japan




5. Public Outreach and Educational Use of the Facility

To raise awareness and interest of Women, Minorities, Middle and High School Students in Engineering and Earthquakes







5. Public Outreach and Educational Use of the Facility

NSF Young Scholar Program: High school students spend 6 weeks in summer in research



5. Public Outreach and Educational Use of the Facility

In Earthquake Engineering Lectures



6. Conclusion

Earthquake Engineering Experimental Facility is essential in seismic rehabilitation since it can

- > provide high quality data that can advance fundamental knowledge of the behavior of geotechnical and structural elements,
- validate analytical models
- help explore development of innovative, cost-effective seismic mitigation technologies
- > encourages educational and outreach activities and awareness of earthquake risk
- demonstrate the important role engineers play in seismic mitigation




Thank you



6.Detection and Long-Term Sustainability of Entrapped Air/Gas

■ Tests performed under hydrostatic, vertical and horizontal hydraulic gradient flow.




Gradient, i


6. Long-Term Sustainability of Entrapped Air/Gas

Evidence on long-term sustainability of air from Mitsu Okamura's study:

- ➤ Tested samples taken from SCP treated sites, after 4 yrs, 8yrs and 26 yrs.
 - > Evaluated degree of saturation.
 - ➤ Air entrapped in the voids of granular soils for a long time.



Soil Improved with Soil Compaction Pile (SCP) Technique from Mitsu Okamura, 2005



from Mitsu Okamura, 2005