Lecture Slides

Chapter 16

Clutches, Brakes, Couplings, and Flywheels

The McGraw-Hill Companies © 2012

Shigley's Mechanical Engineering Design

Ninth Edition

Richard G. Budynas and J. Keith Nisbett

THE REAL PROPERTY OF A CONTRACT OF A CONTRAC

Chapter Outline

16-1	Static Analysis of Clutches and Brakes 827
16-2	Internal Expanding Rim Clutches and Brakes 832
16-3	External Contracting Rim Clutches and Brakes 840
16-4	Band-Type Clutches and Brakes 844
16-5	Frictional-Contact Axial Clutches 845
16-6	Disk Brakes 849
16-7	Cone Clutches and Brakes 853
16-8	Energy Considerations 856
16-9	Temperature Rise 857
16-10	Friction Materials 861
16-11	Miscellaneous Clutches and Couplings 864
16-12	Flywheels 866

Model of Clutch





Shigley's Mechanical Engineering Design



Fig. 16–2

$$N = w_2 \int_0^{w_1} p(u) \, du = p_{\rm av} w_1 w_2 \tag{a}$$

$$w_2 \int_0^{w_1} p(u)u \, du = \bar{u} w_2 \int_0^{w_1} p(u) \, du = p_{\rm av} w_1 w_2 \bar{u} \tag{b}$$

$$\sum F_x = R_x \mp w_2 \int_0^{w_1} fp(u) \, du = 0$$

$$R_x = \pm w_2 \int_0^{w_1} fp(u) \, du = \pm f w_1 w_2 p_{\text{av}}$$
(c)

$$\sum F_y = -F + w_2 \int_0^{w_1} p(u) \, du + R_y = 0$$

$$R_{y} = F - w_{2} \int_{0}^{w_{1}} p(u) \, du = F - p_{\text{av}} w_{1} w_{2} \tag{d}$$

$$\sum M_A = Fb - w_2 \int_0^{w_1} p(u)(c+u) \, du \mp af \, w_2 \int_0^{w_1} p(u) \, du = 0$$

$$F = \frac{w_2}{b} \left[\int_0^{w_1} p(u)(c+u) \, du \pm af \int_0^{w_1} p(u) \, du \right]$$
(e)

$$\int_0^{w_1} p(u)(c+u) \, du - af \int_0^{w_1} p(u) \, du \le 0$$



 $f_{\rm cr} \ge \frac{c + \bar{u}}{a}$

(f)

The doorstop depicted in Fig. 16–2*a* has the following dimensions: a = 4 in, b = 2 in, c = 1.6 in, $w_1 = 1$ in, $w_2 = 0.75$ in, where w_2 is the depth of the pad into the plane of the paper.

(a) For a leftward relative movement of the floor, an actuating force F of 10 lbf, a coefficient of friction of 0.4, use a uniform pressure distribution p_{av} , find R_x , R_y , p_{av} , and the largest pressure p_a .

(b) Repeat part a for rightward relative movement of the floor.

(c) Model the normal pressure to be the "crush" of the pad, much as if it were composed of many small helical coil springs. Find R_x , R_y , p_{av} , and p_a for leftward relative movement of the floor and other conditions as in part *a*.

(d) For rightward relative movement of the floor, is the doorstop a self-acting brake?

(a)

Eq. (c):
$$R_x = f p_{av} w_1 w_2 = 0.4(1)(0.75) p_{av} = 0.3 p_{av}$$

Eq. (d): $R_y = F - p_{av} w_1 w_2 = 10 - p_{av}(1)(0.75) = 10 - 0.75 p_{av}$
Eq. (e): $F = \frac{w_2}{b} \left[\int_0^1 p_{av}(c+u) \, du + af \int_0^1 p_{av} \, du \right]$
 $= \frac{w_2}{b} \left(p_{av} c \int_0^1 du + p_{av} \int_0^1 u \, du + af p_{av} \int_0^1 du \right)$
 $= \frac{w_2 p_{av}}{b} (c+0.5+af) = \frac{0.75}{2} [1.6+0.5+4(0.4)] p_{av}$
 $= 1.3875 p_{av}$

Solving for p_{av} gives

$$p_{\rm av} = \frac{F}{1.3875} = \frac{10}{1.3875} = 7.207 \, \rm psi$$

We evaluate R_x and R_y as

 $R_x = 0.3(7.207) = 2.162$ lbf

$$R_y = 10 - 0.75(7.207) = 4.595$$
 lbf

The normal force N on the pad is $F - R_y = 10 - 4.595 = 5.405$ lbf, upward. The line of action is through the center of pressure, which is at the center of the pad. The friction force is f N = 0.4(5.405) = 2.162 lbf directed to the left. A check of the moments about A gives

$$\sum M_A = Fb - fNa - N(w_1/2 + c)$$

= 10(2) - 0.4(5.405)4 - 5.405(1/2 + 1.6) \delta 0

The maximum pressure $p_a = p_{av} = 7.207$ psi.

Shigley's Mechanical Engineering Design

(b)

Eq. (c):
$$R_x = -fp_{av}w_1w_2 = -0.4(1)(0.75)p_{av} = -0.3p_{av}$$

Eq. (d): $R_y = F - p_{av}w_1w_2 = 10 - p_{av}(1)(0.75) = 10 - 0.75p_{av}$

Eq. (e):
$$F = \frac{w_2}{b} \left[\int_0^1 p_{av}(c+u) \, du + af \int_0^1 p_{av} \, du \right]$$
$$= \frac{w_2}{b} \left(p_{av}c \int_0^1 du + p_{av} \int_0^1 u \, du + af p_{av} \int_0^1 du \right)$$
$$= \frac{0.75}{2} p_{av}[1.6 + 0.5 - 4(0.4)] = 0.1875 p_{av}$$

from which

$$p_{\rm av} = \frac{F}{0.1875} = \frac{10}{0.1875} = 53.33 \,\mathrm{psi}$$

which makes

$$R_x = -0.3(53.33) = -16$$
 lbf

$$R_y = 10 - 0.75(53.33) = -30$$
 lbf

The normal force N on the pad is 10 + 30 = 40 lbf upward. The friction shearing force is fN = 0.4(40) = 16 lbf to the right. We now check the moments about A:

$$M_A = fNa + Fb - N(c + 0.5) = 16(4) + 10(2) - 40(1.6 + 0.5) = 0$$

Note the change in average pressure from 7.207 psi in part *a* to 53.3 psi. Also note how directions of forces have changed. The maximum pressure p_a is the same as p_{av} , which has changed from 7.207 psi to 53.3 psi.

(c) We will model the deformation of the pad as follows. If the doorstop rotates $\Delta\phi$ counterclockwise, the right and left edges of the pad will deform down y_1 and y_2 , respectively (Fig. 16–2b). From similar triangles, $y_1/(r_1 \Delta \phi) = c/r_1$ and $y_2/(r_2 \Delta \phi) = (c + w_1)/r_2$. Thus, $y_1 = c \Delta \phi$ and $y_2 = (c + w_1) \Delta \phi$. This means that y is directly proportional to the horizontal distance from the pivot point A; that is, $y = C_1 v$, where C_1 is a constant (see Fig. 16–2b). Assuming the pressure is directly proportional to deformation, then $p(v) = C_2 v$, where C_2 is a constant. In terms of u, the pressure is $p(u) = C_2(c + u) = C_2(1.6 + u)$.

Eq. (*e*):

$$F = \frac{w_2}{b} \left[\int_0^{w_1} p(u)c \, du + \int_0^{w_1} p(u)u \, du + af \int_0^{w_1} p(u) \, du \right]$$

= $\frac{0.75}{2} \left[\int_0^1 C_2(1.6+u)1.6 \, du + \int_0^1 C_2(1.6+u) \, u \, du + af \int_0^1 C_2(1.6+u) \, du \right]$
= $0.375C_2[(1.6+0.5)1.6+(0.8+0.3333) + 4(0.4)(1.6+0.5)] = 2.945C_2$

Since F = 10 lbf, then $C_2 = 10/2.945 = 3.396$ psi/in, and p(u) = 3.396(1.6 + u). The average pressure is given by

$$p_{\text{av}} = \frac{1}{w_1} \int_0^{w_1} p(u) \, du = \frac{1}{1} \int_0^1 3.396(1.6+u) \, du = 3.396(1.6+0.5) = 7.132 \, \text{psi}$$

The maximum pressure occurs at u = 1 in, and is

$$p_a = 3.396(1.6 + 1) = 8.83$$
 psi

Equations (c) and (d) of Sec. 16–1 are still valid. Thus,

$$R_x = 0.3 p_{av} = 0.3(7.131) = 2.139$$
 lbf
 $R_y = 10 - 0.75 p_{av} = 10 - 0.75(7.131) = 4.652$ lbf

The average pressure is $p_{av} = 7.13$ psi and the maximum pressure is $p_a = 8.83$ psi, which is approximately 24 percent higher than the average pressure. The presumption that the pressure was uniform in part *a* (because the pad was small, or because the arithmetic would be easier?) underestimated the peak pressure. Modeling the pad as a one-dimensional springset is better, but the pad is really a three-dimensional continuum. A theory of elasticity approach or a finite element modeling may be overkill, given uncertainties inherent in this problem, but it still represents better modeling.

(d) To evaluate \bar{u} we need to evaluate two integrations

$$\int_0^c p(u)u \, du = \int_0^1 3.396(1.6 + u)u \, du = 3.396(0.8 + 0.3333) = 3.849 \, \text{lbf}$$

$$\int_0^c p(u) \, du = \int_0^1 3.396(1.6+u) \, du = 3.396(1.6+0.5) = 7.132 \, \text{lbf/in}$$

Thus $\bar{u} = 3.849/7.132 = 0.5397$ in. Then, from Eq. (f) of Sec. 16–1, the critical coefficient of friction is

$$f_{\rm cr} \ge \frac{c + \bar{u}}{a} = \frac{1.6 + 0.5397}{4} = 0.535$$

The doorstop friction pad does not have a high enough coefficient of friction to make the doorstop a self-acting brake. The configuration must change and/or the pad material specification must be changed to sustain the function of a doorstop.

Shigley's Mechanical Engineering Design

An Internal Expanding Centrifugal-acting Rim Clutch



Fig. 16–3

Internal Friction Shoe Geometry



Internal Friction Shoe Geometry



Pressure Distribution Characteristics

- Pressure distribution is sinusoidal
- For short shoe, as in (*a*), the largest pressure on the shoe is *p_a* at the end of the shoe
- For long shoe, as in (*b*), the largest pressure is p_a at $\theta_a = 90^\circ$







$$M_f = \int f \, dN(r - a \, \cos\theta) = \frac{f p_a b r}{\sin\theta_a} \int_{\theta_1}^{\theta_2} \sin\theta(r - a \cos\theta) \, d\theta \qquad (16-2)$$

$$M_N = \int dN(a\sin\theta) = \frac{p_a bra}{\sin\theta_a} \int_{\theta_1}^{\theta_2} \sin^2\theta \, d\theta \tag{16-3}$$

$$F = \frac{M_N - M_f}{c} \tag{16-4}$$

Self-locking condition $M_N > M_f$ (16–5)

$$T = \int fr \, dN = \frac{f p_a b r^2}{\sin \theta_a} \int_{\theta_1}^{\theta_2} \sin \theta \, d\theta$$

=
$$\frac{f p_a b r^2 (\cos \theta_1 - \cos \theta_2)}{\sin \theta_a}$$
 (16-6)

$$R_{x} = \int dN \cos \theta - \int f \, dN \sin \theta - F_{x}$$

$$= \frac{p_{a}br}{\sin \theta_{a}} \left(\int_{\theta_{1}}^{\theta_{2}} \sin \theta \cos \theta \, d\theta - f \int_{\theta_{1}}^{\theta_{2}} \sin^{2} \theta \, d\theta \right) - F_{x}$$

$$R_{y} = \int dN \sin \theta + \int f \, dN \cos \theta - F_{y}$$

$$= \frac{p_{a}br}{\sin \theta_{a}} \left(\int_{\theta_{1}}^{\theta_{2}} \sin^{2} \theta \, d\theta + f \int_{\theta_{1}}^{\theta_{2}} \sin \theta \cos \theta \, d\theta \right) - F_{y}$$

$$(e)$$

$$F = \frac{M_N + M_f}{c}$$
(16-7)
$$R_x = \frac{p_a br}{\sin \theta_a} \left(\int_{\theta_1}^{\theta_2} \sin \theta \cos \theta \, d\theta + f \int_{\theta_1}^{\theta_2} \sin^2 \theta \, d\theta \right) - F_x$$
(f)
$$R_y = \frac{p_a br}{\sin \theta_a} \left(\int_{\theta_1}^{\theta_2} \sin^2 \theta \, d\theta - f \int_{\theta_1}^{\theta_2} \sin \theta \cos \theta \, d\theta \right) - F_y$$
(g)
$$A = \int_{\theta_1}^{\theta_2} \sin \theta \cos \theta \, d\theta = \left(\frac{1}{2} \sin^2 \theta \right)_{\theta_1}^{\theta_2}$$
(16-8)
$$B = \int_{\theta_1}^{\theta_2} \sin^2 \theta \, d\theta = \left(\frac{\theta}{2} - \frac{1}{4} \sin 2\theta \right)_{\theta_1}^{\theta_2}$$
(16-8)
$$R_x = \frac{p_a br}{\sin \theta_a} (A - f B) - F_x$$
(16-9)
$$R_y = \frac{p_a br}{\sin \theta_a} (B + f A) - F_y$$

Shigley's Mechanical Engineering Design

The brake shown in Fig. 16–8 is 300 mm in diameter and is actuated by a mechanism that exerts the same force F on each shoe. The shoes are identical and have a face width of 32 mm. The lining is a molded asbestos having a coefficient of friction of 0.32 and a pressure limitation of 1000 kPa. Estimate the maximum

- (*a*) Actuating force *F*.(*b*) Braking capacity.
- (c) Hinge-pin reactions.



Shigley's Mechanical Engineering Design

(a) The right-hand shoe is self-energizing, and so the force F is found on the basis that the maximum pressure will occur on this shoe. Here $\theta_1 = 0^\circ$, $\theta_2 = 126^\circ$, $\theta_a = 90^\circ$, and $\sin \theta_a = 1$. Also,

$$a = \sqrt{(112)^2 + (50)^2} = 122.7 \text{ mm}$$

Integrating Eq. (16–2) from 0 to θ_2 yields

$$M_{f} = \frac{f p_{a} b r}{\sin \theta_{a}} \left[\left(-r \cos \theta \right)_{0}^{\theta_{2}} - a \left(\frac{1}{2} \sin^{2} \theta \right)_{0}^{\theta_{2}} \right]$$
$$= \frac{f p_{a} b r}{1 - r \cos \theta_{2}} - \frac{a}{2} \sin^{2} \theta_{2}$$

Changing all lengths to meters, we have

 $\sin \theta_a$

$$M_f = (0.32)[1000(10)^3](0.032)(0.150)$$
$$\times \left[0.150 - 0.150 \cos 126^\circ - \left(\frac{0.1227}{2}\right) \sin^2 126^\circ \right]$$
$$= 304 \text{ N} \cdot \text{m}$$

The moment of the normal forces is obtained from Eq. (16–3). Integrating from 0 to θ_2 gives

$$M_N = \frac{p_a bra}{\sin \theta_a} \left(\frac{\theta}{2} - \frac{1}{4} \sin 2\theta\right)_0^{\theta_2}$$

= $\frac{p_a bra}{\sin \theta_a} \left(\frac{\theta_2}{2} - \frac{1}{4} \sin 2\theta_2\right)$
= $[1000(10)^3](0.032)(0.150)(0.1227) \left\{\frac{\pi}{2} \frac{126}{180} - \frac{1}{4} \sin[(2)(126^\circ)]\right\}$
= 788 N · m

From Eq. (16–4), the actuating force is

$$F = \frac{M_N - M_f}{c} = \frac{788 - 304}{100 + 112} = 2.28 \text{ kN}$$

(b) From Eq. (16-6), the torque applied by the right-hand shoe is

$$T_R = \frac{f p_a b r^2 (\cos \theta_1 - \cos \theta_2)}{\sin \theta_a}$$
$$= \frac{0.32 [1000(10)^3] (0.032) (0.150)^2 (\cos 0^\circ - \cos 126^\circ)}{\sin 90^\circ} = 366 \text{ N} \cdot \text{m}$$

The torque contributed by the left-hand shoe cannot be obtained until we learn its maximum operating pressure. Equations (16–2) and (16–3) indicate that the frictional and normal moments are proportional to this pressure. Thus, for the left-hand shoe,

$$M_N = \frac{788 p_a}{1000} \qquad M_f = \frac{304 p_a}{1000}$$

Then, from Eq. (16–7),

$$F = \frac{M_N + M_f}{c}$$

or

$$2.28 = \frac{(788/1000)p_a + (304/1000)p_a}{100 + 112}$$

Shigley's Mechanical Engineering Design

Solving gives $p_a = 443$ kPa. Then, from Eq. (16–6), the torque on the left-hand shoe is

$$T_L = \frac{f p_a b r^2 (\cos \theta_1 - \cos \theta_2)}{\sin \theta_a}$$

Since $\sin \theta_a = \sin 90^\circ = 1$, we have

 $T_L = 0.32[443(10)^3](0.032)(0.150)^2(\cos 0^\circ - \cos 126^\circ) = 162 \text{ N} \cdot \text{m}$ The braking capacity is the total torque:

$$T = T_R + T_L = 366 + 162 = 528 \text{ N} \cdot \text{m}$$

(c) In order to find the hinge-pin reactions, we note that $\sin \theta_a = 1$ and $\theta_1 = 0$. Then Eq. (16–8) gives

$$A = \frac{1}{2}\sin^2\theta_2 = \frac{1}{2}\sin^2 126^\circ = 0.3273$$

$$B = \frac{\theta_2}{2} - \frac{1}{4}\sin 2\theta_2 = \frac{\pi(126)}{2(180)} - \frac{1}{4}\sin[(2)(126^\circ)] = 1.3373$$

Also, let

$$D = \frac{p_a br}{\sin \theta_a} = \frac{1000(0.032)(0.150)}{1} = 4.8 \text{ kN}$$

where $p_a = 1000$ kPa for the right-hand shoe. Then, using Eq. (16–9), we have

$$R_x = D(A - fB) - F_x = 4.8[0.3273 - 0.32(1.3373)] - 2.28 \sin 24^\circ$$
$$= -1.410 \text{ kN}$$
$$R_y = D(B + fA) - F_y = 4.8[1.3373 + 0.32(0.3273)] - 2.28 \cos 24^\circ$$
$$= 4.839 \text{ kN}$$

The resultant on this hinge pin is

$$R = \sqrt{(-1.410)^2 + (4.839)^2} = 5.04 \text{ kN}$$

The reactions at the hinge pin of the left-hand shoe are found using Eqs. (16–10) for a pressure of 443 kPa. They are found to be $R_x = 0.678$ kN and $R_y = 0.538$ kN. The resultant is

$$R = \sqrt{(0.678)^2 + (0.538)^2} = 0.866 \text{ kN}$$

The reactions for both hinge pins, together with their directions, are shown in Fig. 16–9.



Shigley's Mechanical Engineering Design

An External Contracting Clutch-Brake



Fig. 16–10

Notation of External Contracting Shoes



Shigley's Mechanical Engineering Design

Force Analysis for External Contracting Shoes

$$M_f = \frac{f p_a b r}{\sin \theta_a} \int_{\theta_1}^{\theta_2} \sin \theta (r - a \cos \theta) \, d\theta \tag{16-2}$$

$$M_N = \frac{p_a bra}{\sin \theta_a} \int_{\theta_1}^{\theta_2} \sin^2 \theta \, d\theta \tag{16-3}$$

$$F = \frac{M_N + M_f}{c} \tag{16-11}$$

$$R_x = \int dN \cos\theta + \int f \, dN \sin\theta - F_x \tag{a}$$

$$R_y = \int f \, dN \cos\theta - \int dN \sin\theta + F_y \tag{b}$$

$$R_x = \frac{p_a br}{\sin \theta_a} (A + fB) - F_x$$

$$R_y = \frac{p_a br}{\sin \theta_a} (fA - B) + F_y$$

(16 - 12)

Shigley's Mechanical Engineering Design

For counterclockwise rotation:

$$F = \frac{M_N - M_f}{c}$$
(16-13)

$$R_x = \frac{p_a br}{\sin \theta_a} (A - fB) - F_x$$
(16-14)

$$R_y = \frac{p_a br}{\sin \theta_a} (-fA - B) + F_y$$
Brake with Symmetrical Pivoted Shoe



Wear and Pressure with Symmetrical Pivoted Shoe

 $w(\theta) = w_0 \cos \theta$ $w(\theta) = KPVt$ $p(\theta) = \frac{w(\theta)}{KVt} = \frac{w_0 \cos \theta}{KVt}$

 $w_0/(KVt)$ is a constant



Fig. 16–12*b*

 $p(\theta) = (\text{constant})\cos\theta = p_a\cos\theta$

Force Analysis with Symmetrical Pivoted Shoe

$$dN = pbr \, d\theta \tag{d}$$

$$dN = p_a br \cos \theta \, d\theta \tag{e}$$

$$M_f = 2 \int_0^{\theta_2} (f \, dN) (a \cos \theta - r) = 0$$

$$2 f p_a br \int_0^{\theta_2} (a \cos^2 \theta - r \cos \theta) \, d\theta = 0$$

$$a = \frac{4r \sin \theta_2}{2\theta_2 + \sin 2\theta_2} \tag{16-15}$$

Force Analysis with Symmetrical Pivoted Shoe

$$R_{x} = 2 \int_{0}^{\theta_{2}} dN \cos \theta = \frac{p_{a}br}{2} (2\theta_{2} + \sin 2\theta_{2}) \qquad (16-16)$$

$$\int f \, dN \sin \theta = 0$$

$$R_{y} = 2 \int_{0}^{\theta_{2}} f \, dN \cos \theta = \frac{p_{a}brf}{2} (2\theta_{2} + \sin 2\theta_{2}) \qquad (16-17)$$

$$\int dN \sin \theta = 0$$

$$T = afN \qquad (16-18)$$

Notation for Band-Type Clutches and Brakes



Force Analysis for Brake Band

$$(P+dP)\sin\frac{d\theta}{2} + P\sin\frac{d\theta}{2} - dN = 0$$
 (a)

$$dN = Pd\theta \tag{b}$$

$$(P+dP)\cos\frac{d\theta}{2} - P\cos\frac{d\theta}{2} - f\,dN = 0$$
 (c)

$$dP - f \, dN = 0 \tag{d}$$

$$\int_{P_2}^{P_1} \frac{dP}{P} = f \int_0^{\phi} d\theta \quad \text{or} \quad \ln \frac{P_1}{P_2} = f\phi$$
$$\frac{P_1}{P_2} = e^{f\phi} \quad (16-19)$$

Force Analysis for Brake Band

$$T = (P_1 - P_2)\frac{D}{2}$$
(16-20)
$$dN = pbr d\theta$$
(e)
$$P d\theta = pbr d\theta$$

$$p = \frac{P}{br} = \frac{2P}{bD}$$
(16-21)
$$p_a = \frac{2P_1}{bD}$$
(16-22)

Frictional-Contact Axial Single-Plate Clutch



Shigley's Mechanical Engineering Design

Frictional-Contact Axial Multi-Plate Clutch



Fig. 16–15

Geometry of Disk Friction Member



Shigley's Mechanical Engineering Design

Uniform Wear

 $w = f_1 f_2 K P V t$

$$PV = (\text{constant}) = C_1$$

$$pr\omega = C_2$$

$$pr = C_3 = p_{\max}r_i = p_a r_i = p_a \frac{d}{2}$$

$$F = \int_{d/2}^{D/2} 2\pi pr \, dr = \pi p_a d \int_{d/2}^{D/2} dr = \frac{\pi p_a d}{2} (D - d) \qquad (16-23)$$

$$T = \int_{d/2}^{D/2} 2\pi f p r^2 dr = \pi f p_a d \int_{d/2}^{D/2} r \, dr = \frac{\pi f p_a d}{8} (D^2 - d^2) \quad (16-24)$$

$$T = \frac{Ff}{4}(D+d)$$
 (16-25)

Uniform Pressure

$$F = \frac{\pi p_a}{4} (D^2 - d^2) \tag{16-26}$$

$$T = 2\pi f p \int_{d/2}^{D/2} r^2 dr = \frac{\pi f p}{12} (D^3 - d^3)$$
 (16–27)

$$T = \frac{Ff}{3} \frac{D^3 - d^3}{D^2 - d^2} \tag{16-28}$$

Comparison of Uniform Wear with Uniform Pressure



Fig. 16–17

Automotive Disk Brake



Shigley's Mechanical Engineering Design

Geometry of Contact Area of Annular-Pad Brake



Analysis of Annular-Pad Brake

$$w = f_1 f_2 K P V t$$

$$F = \int_{\theta_1}^{\theta_2} \int_{r_i}^{r_o} pr \, dr \, d\theta = (\theta_2 - \theta_1) \int_{r_i}^{r_o} pr \, dr \qquad (16-29)$$

$$T = \int_{\theta_1}^{\theta_2} \int_{r_i}^{r_o} f p r^2 dr d\theta = (\theta_2 - \theta_1) f \int_{r_i}^{r_o} p r^2 dr$$
(16–30)

$$r_{e} = \frac{T}{fF} = \frac{\int_{r_{i}}^{r_{o}} pr^{2} dr}{\int_{r_{i}}^{r_{o}} pr dr}$$
(16–31)

$$M_x = F\bar{r} = \int_{\theta_1}^{\theta_2} \int_{r_i}^{r_o} pr(r\sin\theta) \, dr \, d\theta = (\cos\theta_1 - \cos\theta_2) \int_{r_i}^{r_o} pr^2 \, dr$$

$$\bar{r} = \frac{M_x}{F} = \frac{(\cos\theta_1 - \cos\theta_2)}{\theta_2 - \theta_1} r_e \tag{16-32}$$

Uniform Wear

$$F = (\theta_2 - \theta_1) p_a r_i (r_o - r_i)$$
 (16-33)

$$T = (\theta_2 - \theta_1) f p_a r_i \int_{r_i}^{r_o} r \, dr = \frac{1}{2} (\theta_2 - \theta_1) f p_a r_i \left(r_o^2 - r_i^2 \right)$$
(16-34)

$$r_{e} = \frac{p_{a}r_{i} \int_{r_{i}}^{r_{o}} r \, dr}{p_{a}r_{i} \int_{r_{i}}^{r_{o}} dr} = \frac{r_{o}^{2} - r_{i}^{2}}{2} \frac{1}{r_{o} - r_{i}} = \frac{r_{o} + r_{i}}{2}$$
(16–35)

$$\bar{r} = \frac{\cos\theta_1 - \cos\theta_2}{\theta_2 - \theta_1} \frac{r_o + r_i}{2}$$
(16-36)

Shigley's Mechanical Engineering Design

Uniform Pressure

$$F = (\theta_2 - \theta_1) p_a \int_{r_i}^{r_o} r \, dr = \frac{1}{2} (\theta_2 - \theta_1) p_a \left(r_o^2 - r_i^2 \right) \tag{16-37}$$

$$T = (\theta_2 - \theta_1) f p_a \int_{r_i}^{r_o} r^2 dr = \frac{1}{3} (\theta_2 - \theta_1) f p_a \left(r_o^3 - r_i^3 \right)$$
(16–38)

$$r_{e} = \frac{p_{a} \int_{r_{i}}^{r_{o}} r^{2} dr}{p_{a} \int_{r_{i}}^{r_{o}} r dr} = \frac{r_{o}^{3} - r_{i}^{3}}{3} \frac{2}{r_{o}^{2} - r_{i}^{2}} = \frac{2}{3} \frac{r_{o}^{3} - r_{i}^{3}}{r_{o}^{2} - r_{i}^{2}}$$
(16-39)

$$\bar{r} = \frac{\cos\theta_1 - \cos\theta_2}{\theta_2 - \theta_1} \frac{2}{3} \frac{r_o^3 - r_i^3}{r_o^2 - r_i^2} = \frac{2}{3} \frac{r_o^3 - r_i^3}{r_o^2 - r_i^2} \frac{\cos\theta_1 - \cos\theta_2}{\theta_2 - \theta_1}$$
(16-40)

Two annular pads, $r_i = 3.875$ in, $r_o = 5.50$ in, subtend an angle of 108°, have a coefficient of friction of 0.37, and are actuated by a pair of hydraulic cylinders 1.5 in in diameter. The torque requirement is 13 000 lbf \cdot in. For uniform wear

(a) Find the largest normal pressure p_a .

(*b*) Estimate the actuating force *F*.

(c) Find the equivalent radius r_e and force location \bar{r} .

(d) Estimate the required hydraulic pressure.

Solution

(a) From Eq. (16–34), with T = 13000/2 = 6500 lbf \cdot in for each pad,

$$p_a = \frac{2T}{(\theta_2 - \theta_1) f r_i \left(r_o^2 - r_i^2\right)}$$
$$= \frac{2(6500)}{(144^\circ - 36^\circ)(\pi/180)0.37(3.875)(5.5^2 - 3.875^2)} = 315.8 \text{ psi}$$

(b) From Eq. (16–33),

$$F = (\theta_2 - \theta_1) p_a r_i (r_o - r_i) = (144^\circ - 36^\circ) (\pi/180) 315.8(3.875) (5.5 - 3.875)$$

= 3748 lbf

(c) From Eq. (16–35),

$$r_e = \frac{r_o + r_i}{2} = \frac{5.50 + 3.875}{2} = 4.688$$
 in

From Eq. (16-36),

$$\bar{r} = \frac{\cos\theta_1 - \cos\theta_2}{\theta_2 - \theta_1} \frac{r_o + r_i}{2} = \frac{\cos 36^\circ - \cos 144^\circ}{(144^\circ - 36^\circ)(\pi/180)} \frac{5.50 + 3.875}{2}$$
$$= 4.024 \text{ in}$$

(d) Each cylinder supplies the actuating force, 3748 lbf.

$$p_{\text{hydraulic}} = \frac{F}{A_P} = \frac{3748}{\pi (1.5^2/4)} = 2121 \text{ psi}$$

Geometry of Circular Pad Caliper Brake



Analysis of Circular Pad Caliper Brake

$r_e = \delta e$	(16–41)
$F = \pi R^2 p_{\rm av}$	(16–42)
$T = f F r_e$	(16–43)

Table 16-1

Parameters for a Circular-Pad Caliper Brake

Source: G. A. Fazekas, "On Circular Spot Brakes," *Trans.* ASME, J. Engineering for Industry, vol. 94, Series B, No. 3, August 1972, pp. 859–863.

$\frac{R}{e}$	$\delta = rac{\mathbf{r_e}}{\mathbf{e}}$	P _{max} P _{av}
0.0	1.000	1.000
0.1	0.983	1.093
0.2	0.969	1.212
0.3	0.957	1.367
0.4	0.947	1.578
0.5	0.938	1.875

A button-pad disk brake uses dry sintered metal pads. The pad radius is $\frac{1}{2}$ in, and its center is 2 in from the axis of rotation of the $3\frac{1}{2}$ -in-diameter disk. Using half of the largest allowable pressure, $p_{\text{max}} = 350$ psi, find the actuating force and the brake torque. The coefficient of friction is 0.31.

Solution

Since the pad radius R = 0.5 in and eccentricity e = 2 in,

$$\frac{R}{e} = \frac{0.5}{2} = 0.25$$

From Table 16–1, by interpolation, $\delta = 0.963$ and $p_{\text{max}}/p_{\text{av}} = 1.290$. It follows that the effective radius *e* is found from Eq. (16–41):

$$r_e = \delta e = 0.963(2) = 1.926$$
 in

and the average pressure is

$$p_{\rm av} = \frac{p_{\rm max}/2}{1.290} = \frac{350/2}{1.290} = 135.7 \, \rm psi$$

The actuating force F is found from Eq. (16–42) to be

$$F = \pi R^2 p_{\text{av}} = \pi (0.5)^2 135.7 = 106.6 \,\text{lbf}$$
 (one side)

The brake torque T is

 $T = f F r_e = 0.31(106.6)1.926 = 63.65 \, \text{lbf} \cdot \text{in}$ (one side)

Cone Clutch



Contact Area of Cone Clutch



Uniform Wear

$$p = p_a \frac{d}{2r} \tag{a}$$

$$F = \int p \, dA \sin \alpha = \int_{d/2}^{D/2} \left(p_a \frac{d}{2r} \right) \left(\frac{2\pi r \, dr}{\sin \alpha} \right) (\sin \alpha)$$

$$= \pi p_a d \int_{d/2}^{D/2} dr = \frac{\pi p_a d}{2} (D - d)$$
 (16-44)

$$T = \int rfp \, dA = \int_{d/2}^{D/2} (rf) \left(p_a \frac{d}{2r} \right) \left(\frac{2\pi r \, dr}{\sin \alpha} \right)$$

$$= \frac{\pi f p_a d}{\sin \alpha} \int_{d/2}^{D/2} r \, dr = \frac{\pi f p_a d}{8 \sin \alpha} (D^2 - d^2)$$
 (16-45)

$$T = \frac{Ff}{4\sin\alpha}(D+d) \tag{16-46}$$

Uniform Pressure

$$F = \int p_a \, dA \sin \alpha = \int_{d/2}^{D/2} (p_a) \left(\frac{2\pi r \, dr}{\sin \alpha}\right) (\sin \alpha) = \frac{\pi p_a}{4} (D^2 - d^2) \quad (16-47)$$
$$T = \int rfp_a \, dA = \int_{d/2}^{D/2} (rfp_a) \left(\frac{2\pi r \, dr}{\sin \alpha}\right) = \frac{\pi fp_a}{12\sin \alpha} (D^3 - d^3) \quad (16-48)$$

$$T = \frac{Ff}{3\sin\alpha} \frac{D^3 - d^3}{D^2 - d^2}$$
(16-49)

Energy Considerations

$$I_1\ddot{\theta}_1 = -T \tag{a}$$

$$I_2\ddot{\theta}_2 = T \tag{b}$$

$$\dot{\theta}_1 = -\frac{T}{I_1}t + \omega_1 \tag{c}$$

$$\dot{\theta}_2 = \frac{T}{I_2}t + \omega_2 \tag{d}$$

$$\dot{\theta} = \dot{\theta}_1 - \dot{\theta}_2 = -\frac{T}{I_1}t + \omega_1 - \left(\frac{T}{I_2}t + \omega_2\right)$$

$$= \omega_1 - \omega_2 - T\left(\frac{I_1 + I_2}{I_1I_2}\right)t$$
(16-50)

Energy Considerations

$$t_1 = \frac{I_1 I_2 (\omega_1 - \omega_2)}{T (I_1 + I_2)} \tag{16-51}$$

$$u = T\dot{\theta} = T\left[\omega_1 - \omega_2 - T\left(\frac{I_1 + I_2}{I_1 I_2}\right)t\right]$$
(e)

$$E = \int_{0}^{t_{1}} u \, dt = T \int_{0}^{t_{1}} \left[\omega_{1} - \omega_{2} - T \left(\frac{I_{1} + I_{2}}{I_{1}I_{2}} \right) t \right] dt$$

$$= \frac{I_{1}I_{2}(\omega_{1} - \omega_{2})^{2}}{2(I_{1} + I_{2})}$$
(16-52)

$$H = \frac{E}{9336}$$
(16–53)

Shigley's Mechanical Engineering Design

$$\Delta T = \frac{H}{C_p W} \tag{16-54}$$

where ΔT = temperature rise, °F

 C_p = specific heat capacity, Btu/(lb_m · °F); use 0.12 for steel or cast iron

W = mass of clutch or brake parts, lbm

$$\Delta T = \frac{E}{C_p m} \tag{16-55}$$

where ΔT = temperature rise, °C C_p = specific heat capacity; use 500 J/kg · °C for steel or cast iron m = mass of clutch or brake parts, kg

Shigley's Mechanical Engineering Design

Newton's Cooling Model

$$\frac{T - T_{\infty}}{T_1 - T_{\infty}} = \exp\left(-\frac{\hbar_{\rm CR}A}{WC_p}t\right)$$

(16 - 56)

where

T =temperature at time t, °F

 $T_1 = \text{initial temperature, }^\circ \mathbf{F}$

 T_{∞} = environmental temperature, °F

 \hbar_{CR} = overall coefficient of heat transfer, Btu/(in² · s · °F)

A =lateral surface area, in²

W = mass of the object, lbm

 C_p = specific heat capacity of the object, Btu/(lbm · °F)

Effect of Braking on Temperature



$$H_{\rm loss} = \hbar_{\rm CR} A (T - T_{\infty}) = (h_r + f_v h_c) A (T - T_{\infty})$$
(16-57)

where
$$H_{\text{loss}} = \text{rate of energy loss, Btu/s}$$

 $\hbar_{\text{CR}} = \text{overall coefficient of heat transfer, Btu/(in^2 \cdot s \cdot ^{\circ}\text{F})}$
 $h_r = \text{radiation component of } \hbar_{\text{CR}}, \text{Btu/(in}^2 \cdot s \cdot ^{\circ}\text{F}), \text{Fig. 16-24}a$
 $h_c = \text{convective component of } \hbar_{\text{CR}}, \text{Btu/(in}^2 \cdot s \cdot ^{\circ}\text{F}), \text{Fig. 16-24}a$
 $f_v = \text{ventilation factor, Fig. 16-24}b$
 $T = \text{disk temperature, } ^{\circ}\text{F}$
 $T_{\infty} = \text{ambient temperature, } ^{\circ}\text{F}$

Heat-Transfer Coefficient in Still Air



Shigley's Mechanical Engineering Design
Ventilation Factors



Forced ventilation velocity (ft/s)

Fig. 16–24*b*

Energy Analysis

$$E = \frac{1}{2} \frac{I}{9336} \left(\omega_o^2 - \omega_f^2 \right)$$
(16–58)

$$\Delta T = \frac{E}{WC} \tag{16-59}$$

$$\frac{T_{\min} - T_{\infty}}{T_{\max} - T_{\infty}} = \exp(-\beta t_1)$$

$$T_{\max} = T_{\infty} + \frac{\Delta T}{1 - \exp(-\beta t_1)} \tag{16-60}$$

A caliper brake is used 24 times per hour to arrest a machine shaft from a speed of 250 rev/min to rest. The ventilation of the brake provides a mean air speed of 25 ft/s. The equivalent rotary inertia of the machine as seen from the brake shaft is 289 lbm \cdot in \cdot s. The disk is steel with a density $\gamma = 0.282$ lbm/in³, a specific heat capacity of 0.108 Btu/(lbm $\cdot {}^{\circ}F)$, a diameter of 6 in, a thickness of $\frac{1}{4}$ in. The pads are dry sintered metal. The lateral area of the brake surface is 50 in². Find T_{max} and T_{min} for the steady-state operation.

Solution

$$t_1 = 60^2/24 = 150 \text{ s}$$

Assuming a temperature rise of $T_{\text{max}} - T_{\infty} = 200^{\circ}$ F, from Fig. 16–24*a*,

$$h_r = 3.0(10^{-6}) \text{ Btu/(in}^2 \cdot \text{s} \cdot ^\circ \text{F})$$

$$h_c = 2.0(10^{-6}) \text{ Btu/(in}^2 \cdot \text{s} \cdot ^\circ \text{F})$$
Fig. 16–24b
$$f_v = 4.8$$

 $\hbar_{\rm CR} = h_r + f_v h_c = 3.0(10^{-6}) + 4.8(2.0)10^{-6} = 12.6(10^{-6}) \text{ Btu/(in}^2 \cdot \text{s} \cdot \text{°F)}$

Shigley's Mechanical Engineering Design

The mass of the disk is

$$W = \frac{\pi \gamma D^2 h}{4} = \frac{\pi (0.282)6^2 (0.25)}{4} = 1.99 \text{ lbm}$$

Eq. (16–58): $E = \frac{1}{2} \frac{I}{9336} \left(\omega_o^2 - \omega_f^2 \right) = \frac{289}{2(9336)} \left(\frac{2\pi}{60} 250 \right)^2 = 10.6 \text{ Btu}$
 $\beta = \frac{\hbar_{\text{CR}} A}{W C_p} = \frac{12.6(10^{-6})50}{1.99(0.108)} = 2.93(10^{-3}) \text{ s}^{-1}$

Eq. (16–59):
$$\Delta T = \frac{E}{WC_p} = \frac{10.6}{1.99(0.108)} = 49.3^{\circ}F$$

Eq. (16–60): $T_{\text{max}} = 70 + \frac{49.3}{1 - \exp[-2.93(10^{-3})150]} = 209^{\circ}\text{F}$

$$T_{\rm min} = 209 - 49.3 = 160^{\circ} {\rm F}$$

The predicted temperature rise here is $T_{\text{max}} - T_{\infty} = 139^{\circ}\text{F}$. Iterating with revised values of h_r and h_c from Fig. 16–24*a*, we can make the solution converge to $T_{\text{max}} = 220^{\circ}\text{F}$ and $T_{\text{min}} = 171^{\circ}\text{F}$.

Table 16–3 for dry sintered metal pads gives a continuous operating maximum temperature of 570–660°F. There is no danger of overheating.

Area of Friction Material for Average Braking Power

Table 16-2

Area of Friction Material Required for a Given Average Braking Power Sources: M. J. Neale, *The Tribology Handbook*, Butterworth, London, 1973; *Friction Materials for Engineers*, Ferodo Ltd., Chapel-en-le-frith, England, 1968.

		Ratio of Area to Average Braking Power, in ² /(Btu/s)			
Duty Cycle	Typical Applications	Band and Drum Brakes	Plate Disk Brakes	Caliper Disk Brakes	
Infrequent	Emergency brakes	0.85	2.8	0.28	
Intermittent	Elevators, cranes, and winches	2.8	7.1	0.70	
Heavy-duty	Excavators, presses	5.6-6.9	13.6	1.41	

Characteristics of Friction Materials

	Friction	Maximum	Maximum Temperature		Maximum	
Material	Coefficient <i>f</i>	Pressure p _{max} , psi	Instantaneous, °F	Continuous, °F	Velocity V _{max} , ft/min	Applications
Cermet	0.32	150	1500	750		Brakes and clutches
Sintered metal (dry)	0.29-0.33	300-400	930–1020	570-660	3600	Clutches and caliper disk brakes
Sintered metal (wet)	0.06-0.08	500	930	570	3600	Clutches
Rigid molded asbestos (dry)	0.35-0.41	100	660-750	350	3600	Drum brakes and clutches
Rigid molded asbestos (wet)	0.06	300	660	350	3600	Industrial clutches
Rigid molded asbestos pads	0.31-0.49	750	930-1380	440-660	4800	Disk brakes
Rigid molded nonasbestos	0.33-0.63	100-150		500-750	4800-7500	Clutches and brakes
Semirigid molded asbestos	0.37-0.41	100	660	300	3600	Clutches and brakes
Flexible molded asbestos	0.39-0.45	100	660-750	300-350	3600	Clutches and brakes
Wound asbestos yarn and wire	0.38	100	660	300	3600	Vehicle clutches
Woven asbestos yarn and wire	0.38	100	500	260	3600	Industrial clutches and brakes
Woven cotton	0.47	100	230	170	3600	Industrial clutches and brakes
Resilient paper (wet)	0.09–0.15	400	300		<i>PV</i> < 500 000 psi · ft/min	Clutches and transmission bands

Table 16–3

Some Properties of Brake Linings

	Woven Lining	Molded Lining	Rigid Block
Compressive strength, kpsi	10–15	10–18	10–15
Compressive strength, MPa	70–100	70–125	70-100
Tensile strength, kpsi	2.5–3	4–5	3–4
Tensile strength, MPa	17–21	27-35	21-27
Max. temperature, °F	400-500	500	750
Max. temperature, °C	200-260	260	400
Max. speed, ft/min	7500	5000	7500
Max. speed, m/s	38	25	38
Max. pressure, psi	50-100	100	150
Max. pressure, kPa	340-690	690	1000
Frictional coefficient, mean	0.45	0.47	0.40–45

Table 16–4

Table 16-5

Friction Materials for Clutches

	Friction Coefficient		Max. Temperature		Max. Pressure	
Material	Wet	Dry	°F	°C	psi	kPa
Cast iron on cast iron	0.05	0.15-0.20	600	320	150-250	1000–1750
Powdered metal* on cast iron	0.05-0.1	0.1–0.4	1000	540	150	1000
Powdered metal* on hard steel	0.05-0.1	0.1–0.3	1000	540	300	2100
Wood on steel or cast iron	0.16	0.2–0.35	300	150	60–90	400-620
Leather on steel or cast iron	0.12	0.3–0.5	200	100	10–40	70–280
Cork on steel or cast iron	0.15-0.25	0.3–0.5	200	100	8-14	50-100
Felt on steel or cast iron	0.18	0.22	280	140	5-10	35-70
Woven asbestos* on steel or cast iron	0.1–0.2	0.3–0.6	350-500	175–260	50-100	350-700
Molded asbestos* on steel or cast iron	0.08-0.12	0.2–0.5	500	260	50-150	350-1000
Impregnated asbestos* on steel or cast iron	0.12	0.32	500-750	260-400	150	1000
Carbon graphite on steel	0.05-0.1	0.25	700–1000	370–540	300	2100

- Characteristics of positivecontact clutches
 - No slip
 - No heat generated
 - Cannot be engaged at high speeds
 - Sometimes cannot be engaged when both shafts are at rest
 - Engagement is accompanied by shock



Overload Release Clutch



Fig. 16–25*b*

Shigley's Mechanical Engineering Design

Shaft Couplings

Figure 16-26

Shaft couplings. (a) Plain. (b) Light-duty toothed coupling. (c) BOST-FLEX® through-bore design having elastomer insert to transmit torque by compression; insert permits 1° misalignment. (d) Three-jaw coupling available with bronze, rubber, or polyurethane insert to minimize vibration. (Reproduced by permission, Boston Gear Division, Colfax Corp.)





(a)

(c)



Fig. 16–26

Flywheels



$$\sum M = T_i(\theta_i, \dot{\theta}_i) - T_o(\theta_o, \dot{\theta}_o) - I\ddot{\theta} = 0$$

$$I\ddot{\theta} = T_i(\theta_i, \omega_i) - T_o(\theta_o, \omega_o)$$

$$I\ddot{\theta} = T_i(\theta, \omega) - T_o(\theta, \omega)$$
(a)
(b)

Hypothetical Flywheel Case



Kinetic Energy

$$E_1 = \frac{1}{2} I \omega_1^2 \tag{e}$$
$$E_2 = \frac{1}{2} I \omega_2^2 \tag{f}$$

$$E_2 - E_1 = \frac{1}{2} I \left(\omega_2^2 - \omega_1^2 \right)$$
 (16-61)



Engine Torque for One Cylinder Cycle

Shigley's Mechanical Engineering Design

Coefficient of Speed Fluctuation, C_s

$$C_s = \frac{\omega_2 - \omega_1}{\omega}$$
(16-62)
$$\omega = \frac{\omega_2 + \omega_1}{2}$$
(16-63)

Energy Change

$$E_{2} - E_{1} = \frac{1}{2}I(\omega_{2}^{2} - \omega_{1}^{2})$$
(16-61)

$$E_{2} - E_{1} = \frac{I}{2}(\omega_{2} - \omega_{1})(\omega_{2} + \omega_{1})$$

$$\omega_{2} - \omega_{1} = C_{s}\omega \text{ and } \omega_{2} + \omega_{1} = 2\omega$$

$$E_2 - E_1 = C_s I \omega^2 \tag{16-64}$$

Table 16–6 lists values of the torque used to plot Fig. 16–28. The nominal speed of the engine is to be 250 rad/s.

(*a*) Integrate the torque-displacement function for one cycle and find the energy that can be delivered to a load during the cycle.

(b) Determine the mean torque T_m (see Fig. 16–28).

(c) The greatest energy fluctuation is approximately between $\theta = 15^{\circ}$ and $\theta = 150^{\circ}$ on the torque diagram; see Fig. 16–28 and note that $T_o = -T_m$. Using a coefficient of speed fluctuation $C_s = 0.1$, find a suitable value for the flywheel inertia. (d) Find ω_2 and ω_1 .

Solution

(a) Using n = 48 intervals of $\Delta \theta = 4\pi/48$, numerical integration of the data of Table 16–6 yields E = 3368 in \cdot lbf. This is the energy that can be delivered to the load.

Shigley's Mechanical Engineering Design

θ, deg	<i>T,</i> Ibf∙in	θ, deg	<i>T,</i> Ibf∙in	θ, deg	<i>T,</i> lbf • in	θ, deg	<i>T,</i> Ibf∙in
0	0	195	-107	375	-85	555	-107
15	2800	210	-206	390	-125	570	-206
30	2090	225	-260	405	-89	585	-292
45	2430	240	-323	420	8	600	-355
60	2160	255	-310	435	126	615	-371
75	1840	270	-242	450	242	630	-362
90	1590	285	-126	465	310	645	-312
105	1210	300	-8	480	323	660	-272
120	1066	315	89	495	280	675	-274
135	803	330	125	510	206	690	-548
150	532	345	85	525	107	705	-760
165	184	360	0	540	0	720	0
180	0						

(b) $T_m = \frac{3368}{4\pi} = 268 \, \text{lbf} \cdot \text{in}$

(c) The largest positive loop on the torque-displacement diagram occurs between $\theta = 0^{\circ}$ and $\theta = 180^{\circ}$. We select this loop as yielding the largest speed change. Subtracting 268 lbf \cdot in from the values in Table 16–6 for this loop gives, respectively, -268, 2532, 1822, 2162, 1892, 1572, 1322, 942, 798, 535, 264, -84, and -268 lbf \cdot in. Numerically integrating $T - T_m$ with respect to θ yields $E_2 - E_1 = 3531$ lbf \cdot in. We now solve Eq. (16–64) for *I*. This gives

$$I = \frac{E_2 - E_1}{C_s \omega^2} = \frac{3531}{0.1(250)^2} = 0.565 \, \text{lbf} \cdot \text{s}^2 \text{ in}$$

(d) Equations (16–62) and (16–63) can be solved simultaneously for ω_2 and ω_1 . Substituting appropriate values in these two equations yields

$$\omega_2 = \frac{\omega}{2}(2 + C_s) = \frac{250}{2}(2 + 0.1) = 262.5 \text{ rad/s}$$

$$\omega_1 = 2\omega - \omega_2 = 2(250) - 262.5 = 237.5$$
 rad/s

These two speeds occur at $\theta = 180^{\circ}$ and $\theta = 0^{\circ}$, respectively.

Shigley's Mechanical Engineering Design

Punch-Press Torque Demand



Punch-Press Analysis

$$T(\theta_{1} - 0) = \frac{1}{2}I(\omega_{1}^{2} - \omega_{2}^{2}) = E_{2} - E_{1}$$
$$W = \int_{\theta_{1}}^{\theta_{2}} [T(\theta) - T] d\theta = \frac{1}{2}I(\omega_{\max}^{2} - \omega_{\min}^{2})$$

$$W = \frac{1}{2}I(\omega_{\max}^2 - \omega_{\min}^2) = \frac{I}{2}(\omega_{\max} - \omega_{\min})(\omega_{\max} + \omega_{\min})$$
$$= \frac{I}{2}(C_s\bar{\omega})(2\omega_0) = IC_s\bar{\omega}\omega_0$$

When the speed fluctuation is low,

$$\omega_0 \doteq \bar{\omega}$$
, and
 $I = \frac{W}{C_s \bar{\omega}^2}$

Induction Motor Characteristics

$$T = a\omega + b$$

$$a = \frac{T_r - T_s}{\omega_r - \omega_s} = \frac{T_r}{\omega_r - \omega_s} = -\frac{T_r}{\omega_s - \omega_r}$$

$$b = \frac{T_r \omega_s - T_s \omega_r}{\omega_s - \omega_r} = \frac{T_r \omega_s}{\omega_s - \omega_r}$$
(16-65)

Acceleration:

$$I\ddot{\theta} = T_M \text{ (i.e., } T d\omega/dt = T_M)$$

$$\int_{t_1}^{t_2} dt = \int_{\omega_r}^{\omega_2} \frac{I \, d\omega}{T_M} = I \int_{\omega_r}^{\omega_2} \frac{d\omega}{a\omega + b} = \frac{I}{a} \ln \frac{a\omega_2 + b}{a\omega_r + b} = \frac{I}{a} \ln \frac{T_2}{T_r}$$

$$t_2 - t_1 = \frac{I}{a} \ln \frac{T_2}{T_r} \qquad (16-66)$$

Deceleration:

$$\int_{0}^{t_{1}} dt = I \int_{\omega_{2}}^{\omega_{r}} \frac{d\omega}{T_{M} - T_{L}} = I \int_{\omega_{2}}^{\omega_{r}} \frac{d\omega}{a\omega + b - T_{L}} = \frac{I}{a} \ln \frac{a\omega_{r} + b - T_{L}}{a\omega_{2} + b - T_{L}}$$
$$t_{1} = \frac{I}{a} \ln \frac{T_{r} - T_{L}}{T_{2} - T_{L}}$$
(16-67)

Shigley's Mechanical Engineering Design

Induction Motor Characteristics

$$\frac{T_2}{T_r} = \left(\frac{T_L - T_r}{T_L - T_2}\right)^{(t_2 - t_1)/t_1}$$
(16-68)
$$I = \frac{a(t_2 - t_1)}{\ln(T_2/T_r)}$$
(16-69)