

11 B-Trees

Copyright © 2004, Binnur Kurt

Content

- ▶ Introduction to multilevel indexing and B-trees
- ▶ Insertion in B Trees
- ▶ Search and Insert Algorithms
- ▶ Deletion in B Trees

File Organization

270

Introduction to Multilevel Indexing and B-Trees

- ▶ Problems with simple indexes that are kept in disk:
1. Seeking the index is still slow (binary searching):
 - We do not want more than 3/4 seeks for a search
 - So, here $\log_2(N+1)$ is still slow:

N	$\log_2(N+1)$
15 keys	4
1,000	~10
100,000	~17
1,000,000	~20

File Organization

271

Introduction to Multilevel Indexing and B-Trees

- ▶ Problems with simple indexes that are kept in disk:
2. Insertions and deletions should be as fast as searches:
 - In simple indexes, insertion or deletion take $O(n)$ disk accesses (since index should be kept sorted)

File Organization

272

Indexing with Binary Search Trees

- ▶ We could use balanced binary search trees:
- ▶ **AVL** Trees
 - Worst-case search is $1.44 \times \log_2(N+2)$
 - 1,000,000 keys → 29 Levels
 - Still prohibitive
- ▶ **Paged Binary** Trees
 - Place subtree of size K in a single page
 - Worst-case search is $\log_{K+1}(N+1)$
 - $K=511$, $N=134,217,727$
 - Binary trees: 27 seeks, Paged Binary tree: 3 seeks
 - This is good but there are lots of difficulties in maintaining (doing insertions and deletions) in a paged binary tree

File Organization

273

Multilevel Indexing


- ▶ Consider our 8,000,000 example with keysize = 10B
- ▶ Index file size = 80 MB
- ▶ Each record in the index will contain 100 pairs (key,reference)
- ▶ A simple index would contain: 80,000 records: Too expensive to search (~16 seeks)

File Organization

274

Multilevel Index


- Build an index of an index file
- How?
 - Build a simple index for the file, sorting keys using the method for external sorting previously studied
 - Build an index for this index
 - Build another index for the previous index, and so on
 - The index of an index stores the largest in the record it is pointing to.



B-Trees


- Again an index record may contain 100 keys
- An index record may be half full (each index record may have from 50 to 100 keys)
- When insertion in an index record causes it to overflow
 - Split record in two
 - “Promote” the largest key in one of the records to the upper level

Example for Order = 4




Inserting X







- X is between T and Z: insertion in node 3 splits it and generates a promotion of node X









Promotion



- Important: If Node 1 was full, this would generate a new split-promotion of Node 1. This could be propagated up to the root





Worst-case Search Depth

► The worst-case depth occurs when every node has the minimum number of children

Level	Minimum number of keys (children)
1 (root)	2
2	$2 \cdot \lceil m/2 \rceil$
3	$2 \cdot \lceil m/2 \rceil \cdot \lceil m/2 \rceil = 2 \cdot \lceil m/2 \rceil^2$
4	$2 \cdot \lceil m/2 \rceil^3$
...	...
d	$2 \cdot \lceil m/2 \rceil^{d-1}$

B-Trees 11 File Organization 293

Example

► Assume that we have N keys in the leaves

$$N \geq 2 \cdot (m/2)^{d-1}$$

So,

$$d \leq 1 + \log_{m/2}(N/2)$$

For $N=1,000,000$ and order $m=512$, we have

$$d \leq 1 + \log_{256}(N/2)$$

$$d \leq 3.37$$

► There is at most 3 levels in a B-tree of order 512 holding 1,000,000 keys.

B-Trees 11 File Organization 294

Outline of Search Algorithm

► Search (KeyType key)

1. Find leaf: find the leaf that could contain key, loading all the nodes in the path from root to leaf into an array in main memory
2. Search for key in the leaf which was loaded into main memory

B-Trees 11 File Organization 295

Deletions from B-Tree

► The rules for deleting a key K from a node n :

1. If n has more than the minimum number of keys and K is not the largest key in n , simply delete K from n .
2. If n has more than the minimum number of keys and K is the largest key in n , delete K from n and modify the higher level indexes to reflect the new largest key in n .
3. If n has exactly the minimum number of keys and one of the siblings has “few enough keys”, **merge n** with its sibling and delete a key from the parent node

B-Trees 11 File Organization 296

Deletions from B-Tree (Con't)







► The rules for deleting a key K from a node n :

4. If n has exactly the minimum number of keys and one of the siblings has extra keys, **redistribute** by moving some keys from a sibling to n , and modify higher levels to reflect the new largest keys in the affected nodes

B-Trees 11 File Organization 297

Example

B-Trees 11 File Organization 298



Implementation

```
typedef struct {
    int Count; // Number of keys stored in the current
    ItemType Key[MaxKeys];
    long Branch[MaxKeysPlusOne];
} NodeType;
```

Implementation (Con't)

```
typedef struct {
    int Count; // Number of keys stored in the current
    ItemType Key[MaxKeys];
    long Branch[MaxKeysPlusOne];
    bool Search(KeyFieldType SearchKey,
                ItemType & Item);
} NodeType;
```

bool Search(KeyFieldType SearchKey,...)

```
{
    long CurrentRoot;
    int Location;
    bool Found;
    Found = false;
    CurrentRoot = Root;
    while ((CurrentRoot != -1L) && (!Found)) {
        fseek(hFile, CurrentRoot * NodeSize, SEEK_SET);
        fread((unsigned char *)(&CurrentNode), NodeSize, 1, hFile);
        if (SearchNode(SearchKey, Location)) {
            Found = true;
            Item = CurrentNode.Key[Location];
        } else CurrentRoot = CurrentNode.Branch[Location + 1];
    }
    return Found;
}
```

bool SearchNode(KeyFieldType Target,...)

```
bool SearchNode(const KeyFieldType Target, int & Location) const {
    bool Found=false;
    if (strcmp(Target, CurrentNode.Key[0].KeyField)<0) Location=-1L;
    else {
        Location = CurrentNode.Count - 1;
        while ((strcmp(Target, CurrentNode.Key[Location].KeyField) < 0)
               && (Location > 0))
            Location--;
        if (strcmp(Target, CurrentNode.Key[Location].KeyField) == 0)
            Found = true;
    }
    return Found;
}
```