

FCTUC DEPARTAMENTO DE ENGENHARIA CIVIL

FACULDADE DE CIÊNCIAS E TECNOLOGIA UNIVERSIDADE DE COIMBRA

Andreia Marques Department of Civil Engineering, University of Coimbra, Portugal.

Paulo Coelho Department of Civil Engineering, University of Coimbra, Portugal.

Ulas Cilingir Department of Engineering, University of Sheffield, UK.

Stuart Haigh Department of Engineering, University of Cambridge, UK.

Gopal Madabhushi Department of Engineering, University of Cambridge, UK.

INTRODUCTION

Research Tools

Centrifuge Experiment

Results





Introduction

RESEARCH TOOLS

Centrifuge Experiment

Results

Future Work

10m Turner Beam Centrifuge



(Photo adapted from Schofield Centre Archive)

Introduction

RESEARCH TOOLS

Centrifuge Experiment

Results

Future Work

SAM actuator



(Photo adapted from Schofield Centre Archive)

Introduction

RESEARCH TOOLS

Centrifuge Experiment

Results

Future Work

ESB container



Introduction

RESEARCH TOOLS

Centrifuge Experiment

Results

Future Work

Automatic Sand Pourer



Model Saturation

Introduction

RESEARCH TOOLS

Centrifuge Experiment

Results



Introduction

RESEARCH TOOLS

Centrifuge Experiment

Results

Future Work

Instrumentation


- Accelerometers (acc);
- Pore Pressure Transducers (PPT);
- Microelectromechanical system accelerometer (MEMS);
- Linear Variable Displacement Transducer (LVDT).

Introduction

Research Tools

CENTRIFUGE EXPERIMENT

Results





Introduction

Research Tools

CENTRIFUGE EXPERIMENT

Results





Introduction

Research Tools

CENTRIFUGE EXPERIMENT

Results


Structure	width (mm)	length (mm)	height (mm)
Н	60	60	24,5
L	60	60	15

Introduction

Research Tools

CENTRIFUGE EXPERIMENT

Results




Introduction

Research Tools

Centrifuge Experiment

RESULTS




Introduction

Research Tools

Centrifuge Experiment

RESULTS



Introduction


Research Tools

Centrifuge Experiment

RESULTS









Introduction


Research Tools

Centrifuge Experiment

RESULTS

Future Work

relative distance from the left wall



Introduction

Research Tools

Centrifuge Experiment

Results

FUTURE Work

- evaluate the development of excess pore pressures during the seismic simulation, post-earthquake response to the high transient hydraulic gradients, and the propagation of the accelerations under the footings and free-field during the seismic motion.
- clarify the importance of the characteristics of the seismic loading on the performance of the soil-structure system, especially by comparing realistic seismic loading with constant amplitude and frequency sinusoidal cyclic loading;
- assess the effectiveness of narrow densified zones with selectively positioned high-capacity vertical drains in the mitigation of earthquake-induced liquefaction effects;
- numerical tools to perform realistic numerical predictions of the behaviour of the shallow foundations affected by seismic loading inducing ground liquefaction.

Introduction

Research Tools

Centrifuge Experiment

Results

Future Work

THE END